

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec 21, 1920 - (DCSO records Vol 25 Pages 10649-50)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S\ 15}{S\ 22}$   
1921

from which

A yew, 14" dia., bears N.34°W., 32 lks., mkd: 1/4 S15 BT.

A hemlock, 7" dia., bears S.11°E., 18 lks., mkd: 1/4 S22 BT.

-----  
U.S. Forest Service, Tiller Ranger District 5/20/1948 -  
(Filed Nov. 16, 1973) - C.S. File 56/40-69

-----  
Found - Brass cap.  
6" W.F. N.11°W., 18 lks. tagged.  
14" Yew, S.34°E., 32 lks.

Note - Best route to cor. use FS Rd. No. 291. Corner should have been destroyed by Rd. #291. Sec. line marker on the Old Buckeye Cr. Trail.