

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 441100

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 3 only; T29-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14089)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 3 only, with brass cap mkd.

¼ S 3  
1937

from which

- A fir, 35" dia., bears S.50°E., 96 lks., mkd: ¼ S3 BT.
- A fir, 20" dia., bears S.35°W., 115 ft., mkd: ¼ S3 BT.

Dennis Gaylord, USFS & DCSO Deputy - Walt Barton - Feb. 24, 1977 - C.S. File 59/29-37

-----  
Found - 1937 GLO brass cap properly stamped. Bent over 90° by logging activities. I removed & straightened pipe. Re-set brass cap by iron pipe monument using accessories. (Township & range not marked on Brass cap.)

A live 27" D.Fir bears S.35°W., 75.9 ft. has healed scar. Placed County BT sign.

A 41" D.Fir stump bears S.50°E., 63.36 ft. has healed scar. Placed a County BT sign on stump.

New BT - A 32" D. Fir bears S.73°E., 54.9 ft. double blazed & scribed "¼ S3 CS BT". Place County BT sign on tree.

Corner is 850 feet east of F.S. Rd. #2930A.