

PRIMARY CORNER DESCRIPTION South cor. Secs. 34 & 35, only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10572-3 & Vol. 26 Page 10971)

Set a conglomerate stone 18x12x6", 12" in the ground for cor. of secs. 2, 3, 34, & 35 mkd with 2 notches on E & 4 notches on W edges, from which
A pine, 28" dia., bears N.76°E., 14 lks., mkd: T29S R1E S35 BT.
A pine, 36" dia. bears S.57°W., 41 lks mkd: T30S R1E S2 BT
A madrone, 10" dia., bears S.56°W., 46 lks., mkd: T30S R1E S3 BT.
A fir, 28" dia. bears N.85°W., 50 lks mkd: T29S R1E S34 BT

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14075-6)

The orig. cor. of secs. 2, 3, 34 & 35, which is a basalt stone, 18x12x6" firmly set, mkd. with 2 notches on E & 4 notches on W edge. Hereafter this cor. will refer to secs. 34 & 35 only.
At point for corner
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with the orig. stone deposited at the base, for cor. of secs. 34 & 35 only, with brass cap mkd
T29S R1E
S 34 | S 35
T30S R1E
S 3
1937

from which
A pine, 28" dia., bears N.76°E., 13 lks., blaze healed. I do not open (Old BT)
A pine, 45" dia., bears S.57°E., 40 lks. mkd. T30S R1E S2 BT. I obliterate the marks on this tree. (Old BT)
A madrona, 11" dia., bears S.57°W., 46 lks., mkd. T30S R1E S3 BT. I obliterate the blaze, healed; I do not open. (Old BT)
A fir, 33" bears N.84°W., 50 lks. blaze healed; I do not open. (Old BT)

Dennis Gaylord, USFS & DCSO Deputy - Chuck LeBold - Joe Sheriff - Feb. 10, 1977 - C.S. file 59/29-28

Found - 1937 GLO brass cap properly stamped.
A rotted Pine stump, bears N.76°E., 8.58 ft. scribing visible "T29S R1E S35 BT" Cont.

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION South cor. Secs. 34 & 35, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 37" D.Fir, bears N.84°W., 33.0 ft. has healed blaze. Placed County BT sign on Fir.

A 41" Ponderosa Pine, bears S.57°E., 26.4 ft. scribing destroyed. Partly healed blaze.

A 16" Madrone, bears S.57°W., 30.36 ft. scribing destroyed. Partly healed scar.

A rotted stump, bears East 5.28 ft. Two hack marks visible on stump. (Line tree).

New BT - An 11" D. Fir, bears N.55°30'E., 58.8 ft. scribed "T29S R1E S35 CS BT". Placed BT sign on Fir.

Compass declination: 18°E