

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page 10582)

Set a conglomerate stone 15x12x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A madrone, 12" dia., bears N.52°E., 18 lks., mkd: ¼ S35 BT
A fir, 18" dia., bears N.42°W., 14 lks., mkd: ¼ S34 BT.

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-26

Never found.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton - 2/24/1977 - C.S. File 59/29-35

Found - Conglomerate stone firmly set 4" above the ground surface marked 1/4 on West face and "X" on top. Stone is 14x9x8".

A D.Fir blown down - Remains of stump bears N.42°W., 9.24 ft. Scribing visible on face of log ¼ S3 BT
Madrone BT to NE is gone.

Set - 2½" Brass cap on a 1"x36" I.P. marked
Douglas County Surveyors

Office
¼ T29S
S 34|S 35
1977 R1E

Orig. corner stone moved aside. Set Brass cap & buried stone alongside.

New BTs- A 21" Sugar Pine bears S.21°30'E.. 38.3 ft. double blazed & scribed "¼ S35 CS BT".

A 21" D.Fir bears N.51°30'W., 41.9 ft. double blazed & scribed "¼ S34 CS BT".

Placed County BT signs on both trees.

Note - Forest Service Rd. #2930 is 200 ft. south of corner. Corner lies on south slope.