

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10582)

-----

Set a conglomerate stone 15x12x8", 10" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 1 notch on S & 2 notches on E edge, from which

- A fir, 16" dia. bears N.70°E., 23 lks mkd: T29S R1E S26 BT
- A fir, 18" dia. bears S.83°E., 10 lks mkd: T29S R1E S35 BT
- A fir, 15" dia. bears S.50°W., 23 lks mkd: T29S R1E S34 BT
- A fir, 8" dia., bears N.49°W., 21 lks mkd: T29S R1E S27 BT

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 10/22/1974 - C.S. File 57/12-1

-----

Found - All orig. BTs alive & well-healed. Also fd. stone fragments with possible chisel marks at the cor. point.

At the cor. point as determined at record measurement from the original bearing trees:

- An Orig. 16" now 24" D.Fir bears N.70°E., 15.2 ft. alive and well-healed.
- An orig. 18" now 22" D.Fir bears S.83°E., 6.6 ft. Alive and well-healed
- An orig. 15" now 23" D.Fir bears S.50°W., 15.2 ft. Alive and well healed.
- An orig. 8" now 12" D.Fir bears N.49°W., 13.9 ft. alive and well healed;

We set - A 1"x30" Iron pipe with brass cap attached mkd.

COUNTY SURVEYORS	T 29 S
OFFICE	S 27   S 26
1974	S 34   S 35
	R 1 E

Compass declination: 20° East.