

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10584-5)

Set a conglomerate stone 15x12x8", 10" in the ground for cor. of secs. 22, 23, 26, & 27 mkd with 2 notches on S & E edges, from which

A fir, 18" dia. bears N.40°E., 67 lks mkd: T29S R1E S23 BT

A fir, 16" dia. bears S.89°E., 66 lks mkd: T29S R1E S26 BT

A fir, 36" dia. bears S.59°W., 87 lks mkd: T29S R1E S27 BT

A fir, 15" dia bears N.13°W., 83 lks mkd: T29S R1W* S22 BT

* Tree scribed R1E per G. Quibell, Doug. Co. Surveyors Office 9/1981 - VL

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10612)

Cor. of secs. 22, 23, 26, & 27, which is a conglomerate stone, 5x12x8" above ground, firmly set, marked & witnessed as described by the surveyor general, except that the NE BT is dead. I take new BT. From corner:

(New BT) A fir, 15" dia., bears N.56°E., 75 lks., mkd: T29S R1E S23 BT.

(Old BT) A fir, 16" dia., bears S.89°E., 66 lks., mkd: T29S R1E S26 BT.

(Old BT) A fir, 36" dia., bears S.59°W., 87 lks., mkd: T29S R1E S27 BT.

(Old BT) A fir, 15" dia., bears N.13°W., 83 lks., mkd: T29S R1E S22 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Peter Earle - 8/27/1974 - C.S. File 57/2-16

Found - A 12"x12"x8" conglomerate stone, (rec. 15x12x8") firmly set in mineral soil and buried under forest duff, mkd. with a "+" on top and 2 notches each on the south and east faces; from which:

An orig 18" now 20" Grand Fir bears N.57°E., 50.0 ft (rec. N.40°E., 44.2 ft.), alive and well-healed showing a good scar.

An orig. 16" now 22" Grand Fir, bears S.89°E., 43.6 ft. alive and well-healed but showing signs of rot at the base.

An orig. 36" now 48" D.Fir, bears S.59°W., 57.4 ft. alive and well-healed showing a good scar.

An orig. 15" Fir, now dawn and well-rotted, bears N.13°W., 54.8 ft. We find fragments of the orig. blaze and illegible scribe marks. cont.

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

This corner lies approx. 30 ft. south of a small stream.
Set - A 1" IP with brass cap attached mkd:

COUNTY SURVEYORS T 29 S
OFFICE S 22 | S 23
S 27 | S 26
1974
R1E

Brass cap set flush with the ground. We place the orig. stone alongside and mark the following bearing trees:

- A 10" D.Fir, bears N.89½°W., 25.1 ft. scribed "T29S R1E S22 CS BT"
- A 10" D.Fir, bears S.10½°E., 26.1 ft. scribed "T29S R1E S26 CS BT".
- A 12" Hemlock bears N.82°E., 36.5 ft. scribed "T29S R1E S23 CS BT".

Note - Compass declination set at 20° East.