

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol 25 Pages 10642-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 10, 11, 14, & 15, with brass cap mkd

T29S | R1E  
S 10 | S 11  
S 15 | S 14  
1921

from which

- A fir, 36" dia., bears N.75°E., 34 lks., mkd: T29S R1E S11 BT.
- A hemlock, 12" dia., bears S.63°E., 26 lks., mkd: T29S R1E S14 BT.
- A fir, 20" dia., bears S.82°W., 40 lks., mkd: T29S R1E S15 BT.
- A hemlock, 10" dia., bears N.67°W., 30 lks., mkd: T29S R1E S10 BT.

U.S. Forest Service, Tiller Ranger District - 1/22/1945 -  
(Filed Nov. 16, 1973) - C.S. File 56/40-54

-----  
Found - Brass cap

- 36" D.F. N.75°E., 26 lks.
- 10" Hemlock, N.67°W., 30 lks.
- 12" Hemlock, S.63°E., 26 lks.
- 20" Fir, S.82°W., 40 lks.

Note - Use Road No. 2942. Follow telephone line toward river should hit sec. line.