

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10645)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 2, 3, 10, & 11, with brass cap mkd

T29S	R1E
S 3	S 2
S 10	S 11

1921

from which

- A fir, 40" dia., bears N.47°E., 31 lks mkd: T29S R1E S2 BT
- A fir, 18" dia. bears S.63°E., 17 lks mkd: T29S R1E S11 BT
- A fir, 18" dia., bears S.4°W., 36 lks mkd: T29S R1E S10 BT
- A fir, 6" dia., bears N.8°W., 44 lks mkd: T29S R1E S3 BT

Douglas Co. Surveyors Office - Gary Langlitz - Clell E. Goodwin, M. Lenora Lading & A.Vic Cangie - 9/4/1975 - C.S. File 57/36-3

(Reported as) Corner not found - Corner appears to fall in Forest Service Rd. #272-1. All evidence has been destroyed. Intersection of blazed lines running North, East & West from the corner also indicate location to be in roadway.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - April 30, 1981 - C.S. File 61/24-2

Found - Orig. 40" now 33" fir stump with well healed scar, I cut into the stump and find the scribed marks "T29S R1E S2 BT" This is the orig. NE BT.

Orig. 18" now 20" fir down and partially rotted with another tree lying on top of it. After removing the top log and cutting into the 20" fir, I find "T29S R1E S10 BT. This is the orig. SW BT.

36" fir stump with old BT tag bears S.23°E., 23.5 ft
No signs of an old face or scribing. (not of rec)
No signs of orig. NW or SE BTs.

Orig. 1921 brass cap appears to be either buried in road fill or gone.

Set - At rec. bearing & dist. (S.46°W., 20.5 ft.) from orig. 40" now 33" fir stump, I set a brass cap. Rec. bearing & dist. to stump hole of orig. 18" now 20" fir (N.4°E. 23.8 ft) fits reasonably well since center of stump hole is hard to define. Brass cap is firmly set 8" above the ground & stamped: DOUGLAS CO SURVEYOR T29S S3 S2 S10 S11 R1E 1981

New BTs- 12" Fir bears N.37°W., 91.3 ft. with "T29S R1E S3 CS BT" scribed in double blaze. cont. next pg.

Alias	Description
Alias	Description
Alias	Description
Alias	Description

6" cedar bears N.83°E., 69.6 ft. with T29S R1E S2 CS BT" scribed in double blaze.
6" cedar bears S.61°E., 45.7 ft. with T29S R1E S11 CS BT" scribed in double blaze.
10" pine bears S.22°W., 37.7 ft. with "T29S R1E S10 CS BT" scribed in double blaze.
All trees have DCSO BT tags.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Stephen J. Flause - June 10, 1991 - C.S. File 59/30 (moved to C.S. File 67/28-28

REFERENCED OUT CORNER ONLY (Orig. monument not found)
Found - A 1"x36" IP with brass cap firmly set protruding 8" above ground. (DCSO, 1981)
Monument and most accessories are in a slide area. Appear to have moved.
Found - 40" Fir now a 33" decaying fir stump with previously opened blaze with reverse scribing "T29S R1E" visible bears N.46°E., 20.0 ft (Rec. N.47°E., 20.5 ft.) Original
12" now 15" Fir with well healed double blaze bears N.39°W., 100 ft. (Rec. N.37°W., 91.3 ft.) to center of root crown (Tree is pistol butt) (1981)
6" now 9" cedar with partially healed double blaze bears N.81°E. 62.5 ft (Rec. N.83°E. 69.6 ft) 1981
6" now 9" cedar with partially healed double blaze bears S.61°E., 39.5 ft. (Rec. 45.7 ft.) (1981)
10" Pine now 10" dia. 8 ft. high stump with scribing "T29S R1E S10 CS BT" visible in unhealed blaze bears S.37°W., 39.0 ft (Rec S.22°W. 37.7 ft) 1981
36" Fir stump 4½ ft. tall with opened area has no sign of blaze or scribing. Has a BT tag. Bears S.19°E., 22.2 ft. Source unknown. (Rec. per 1981, S.23°E., 23.5 ft.)

We remove the monument set by DCSO in 1981 and set a wood hub at this location. We determine a location for the corner at the record bearing and distance from the 15" Fir which bears N.37°W. , 91.3 ft. Nothing set at this location as slide area to be removed. The hub set to mark the found monument location bears S.59°E., 9.32 ft.

Set - To reference corner, WE SET a 5/8"x30" iron rod with alum. cap mkd. "B02", N.37°W., 166.47 ft. and a 5/8"x30" iron rod with alum, cap mkd. "B01", N.3°W., 219.43 ft. Caps mkd. "Douglas Co. Surveyor". (See sketch in C.S. File for observed angle between monuments.) cont. next pg

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

New ties to found accessories:

- 33" decaying Fir stump bears N.68°E., 24.2 ft. (Rec. N.46°E., 20.5 ft.)
- 15" Fir bears N.37°W., 91.3 ft. (Rec. held)
- 9" cedar bears N.86°E. 69.9 ft (Rec N.83°E. 69.6 ft)
- 9" cedar bears S.60½°E., 48.8 ft. (Rec. S.61°E., 45.7 ft.)
- 10" Pine stump bears S.23¼°W., 39.1 ft. (Rec. S.22°W., 37.7 ft)
- 36" tagged Fir stump bears S.30½°E., 30.0 ft. (Rec. S.23°E., 23.5)

Fd. Ok 8/12/1997 - DCSO - C.S. file 64/79-9

Douglas County Surveyors Office - Randall Smith - Stephen Flause - 4/10/2009 - C.S. File 67/28-2

- Found - 5/8" IR/Alum. cap "B01" bears N.4½°W., 219.4 ft. (rec. N.3°W., 219.43 ft) 1991
- 5/8" IR/Alum. cap "B02" bears N.38°W., 166.5 ft. (rec. N.37°W., 166.47 ft.) 1991
- 10" now rotted 8 ft. high pine snag with rotted blaze & illegible scribe mark bears S.23¼°W., 39.1 ft. (agree with 1991 rec.) 1981
- 12" now 17" dia., D.Fir w/a fully healed double blaze bears N.38°W. 91.3 ft (rec. N.37°W., 91.3 ft) 1981
- 6" now 13" dia., I.Cedar with a fully healed double blaze bears N.86°E., 80.6 ft. (1991 rec. N.86°E., 80.6 ft. (1991 rec. N.86°E., 69.9 ft.)
- 36" dia., D.Fir 4 ft. tall D.Fir stump bears S.50°E., 50.0 ft. (1991 rec. S.30½°E., 30.0 ft.) unknown rec.

New - 5/8"x60" long iron rod with DCSO alum. cap marked "2009" is set at position determined by 1991 renewal as shown on front (above). Protrudes 6" out of ground.

23" S.Pine double blazed & scribed "T29S R1E S10 CS BT" bears S.34°W., 45.6 ft.

Note - Corner lies in slide area approx 50 ft. SE'ly of a gravel road. Area now shows signs of slide control work being completed.

Compass decl. 16½°E. See sketch in file.

Previous renewal C.S. File 59/30 has been moved to this CS file