

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10647)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for  
¼ sec. cor., with brass cap marked

¼  
S 3 | S 2  
1921

from which

A fir, 38" dia., bears S.87°E., 20 lks., mkd: ¼ S2 BT.

A cedar, 30" dia., bears S.39°W., 60 lks., mkd: ¼ S3 BT.

-----  
U.S. Forest Service, Tiller Ranger District - No date - (Filed  
Nov. 16, 1973) - C.S. File 56/40-40

-----  
Never found.

-----  
Douglas Co. Surveyors Office - Gregory Quibell, Deputy -  
Debbie Stewart & Terrie Plouff - July 1981 - C.S. 61/27-22

-----  
Found - Orig. GLO Brass Cap bent over to the East flush with  
the ground, marked US General Land Office Survey  
¼ S3 S2 1921

39" Fir (Orig. 36") stump, rotten, with well healed  
blaze, bears S.87°E., 13.2 ft.

34" Cedar (Orig. 30") stump with well healed blaze  
bears S.39°W., 39.6 ft.

Set - I referenced the point the orig. pipe went into the  
ground, then dug up the pipe, straightened it &  
set it back in its orig. position. NO new mon.  
set. Brass Cap now protrudes 12" out of ground  
with a pile of rocks around it.

New BTs - 6" Fir bears N.24°W., 26.0 ft., scribed ¼ S3 CS BT

16" Fir bears N.77°W., 80.0 ft., scribed ¼ S3 CS BT

11" Fir bears N.68°E., 9.3 ft., scribed ¼ S2 CS BT

9" Pine bears N.41°E., 44.7 ft., scribed ¼ S2 CS BT

NOTE - All new BTs scribed in double blazes.

NOTE - All BTs tagged with DCSO BT tags.