

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 501100

PRIMARY CORNER DESCRIPTION (North) CC Secs. 2 & 3 only; T30-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14088-9)

-----  
Set an iron post, 28" long, 2½" dia., 27" in the ground, for closing cor. of secs. 2 & 3, with brass cap marked:

T29S R1E  
-----  
S 35  
-----  
S 3 | S 2  
T30S R1E  
-----  
C | C  
-----  
1937

from which

A Y.Pine, 32" dia., bears S.50°E., 83 lks., mkd: T30S R1E S2 CC BT.

A Y.Pine, 28" dia., bears S.69°W., 64 lks., mkd: T30S R1E S3 CC BT.

... the cor. of secs. 34 & 35 only, S.bdy T29S R1E hereinbefore described, bears N.89°55'W., 1.32 chs.

Dennis Gaylord, USFS & DCSO Deputy - Joe Sheriff - Feb. 10, 1977 - C.S. file 59/29-29

-----  
Found - 1937 GLO Brass cap properly stamped.  
A 31" Ponderosa Pine, bears S.69°W., 42.2 ft. scribing visible on partly healed blaze "T30S R1E S3 CC BT"

The SW BT is blown down. Stump hole bears S.50°E., 54.8 ft. Placed County BT sign on live Pine.

New BT - A 9" Sugar Pine bears S.5°E., 53.2 ft. blazed & scribed "T30S R1E S2 CC CS BT".

Place County BT sign on tree.

Compass declination: 18°E