

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10583)

-----  
Set a basalt stone 18x12x7", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A madrone, 12" dia., bears N.15°W., 18 lks., mkd: ¼ S26 BT  
A fir, 12" dia., bears S.12°E., 29 lks., mkd: ¼ S35 BT.

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-11

-----  
Never found.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton - March 3, 1977 - C.S. File 59/31-2

-----  
Found - 15x10x7" Stone firmly in place marked "1/4" on the north face and "X" on top.  
An 18" D.Fir bears S.12°E., 19.4 ft. (Rec. S.12°E., 19.14 ft.) Has a healed blaze.  
A 14" Madrone bears N.10°30'W., 12.2 ft. (Rec. N.15°W., 11.88 ft.) Scribing visible on partly healed blaze "S2 /4 B"  
Both BTs are alive & in good condition. Placed County BT signs on both trees.  
Set - Moved corner stone aside & set in its place a 2½" Brass Cap on a 1" Gal. I.P. mkd: County Surveyors Office T29S ¼ S26 S35 R1E 1977. Buried corner stone alongside. Brass cap monument set in a mound of stones 2½'x2½'x1' high.  
Note - Corner is 500 ft. more or less, west of Forest Service Rd. #2930.