

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10585)

Set a basalt stone 15x8x6", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
A fir, 12" dia., bears N.46°W., 10 lks., mkd: 1/4 S23 BT.
A fir, 7" dia., bears S.42°E., 10 lks., mkd: 1/4 S26 BT.

Fd. & used on GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10612)

Douglas Co. Surveyors Office - Gary Langlitz - Clell E. Goodwin, M. Lenora Ladig, & A. Vic Cangie - 2/11/1976 - C.S. File 59/2-16

Found - Remains of orig. NW bearing, an orig. 12" D.Fir now a 15" rotted stump with scribing "T" visible.
We also find the original monument, a 15x8x6" stone with "1/4" chiseled on apparent north face. This stone has been disturbed by logging activity.
We find the probable remains of the orig. SE bearing tree but cannot positively identify it.
At the corner point as determined by record bearing and distance from the remains of the orig. NW BT an orig. 12" fir, now a 15" rotted stump bearing N.45°W., 6.6 ft.

Set a 1"x30" IP 26" in the ground with Brass cap attached mkd
DOUGLAS CO. SURVEYOR T29S R1E
1976 1/4 S 23
S 26

We place the orig stone alongside the south edge of the Brass cap with the "1/4" facing west, and mark the following BTs
A 12" Incense cedar bears N.75 1/2°E., 49.7 ft., scribed "1/4 S23 CS BT" on a double blaze.
A 7" G.Fir bears N.22°W., 32.9 ft., scribed "1/4 S 23 CS BT" on a double blaze.

Note: This corner is located approx 150 ft. west of the East edge of an old clearcut.
We also place a location tag approx 550 ft. west of the 1/4 corner near the end of forest Service Road "2921-D.