

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10641)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S\ 14}{S\ 23}$   
1921

from which

A pine, 26" dia., bears N.55°E., 50 lks., mkd: 1/4 S14 BT.

A fir, 20" dia., bears S.61°W., 20 lks., mkd: 1/4 S23 BT.

-----  
U.S. Forest Service, Tiller Ranger District - 1/24/1945 -  
(Filed Nov. 16, 1973) - C.S. File 56/40-67

-----  
Found - Brass cap  
26" SP N.55°E., 50 lks.  
30" DF S.61°W., 20 lks. tagged

Note - Best route to cor. use F.S. Road No. 291 or 2921.  
Corner could lie in C.C.