

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10646)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S \ 2}{S \ 11}$
1921

from which

A fir, 20" dia., bears N.42°E., 40 lks., mkd: 1/4 S2 BT.

A fir, 50" dia., bears S.44°W., 33 lks., mkd: 1/4 S11 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 8/1/1974 - C.S. File 57/2-10

Found - 1921 US GLO Brass cap properly marked. From which:
A Orig. 20" now 24" Fir, bears N.46°E., 28.2 ft. (rec. N.42°E., 26.4 ft.) with well healed scar
A orig. 50" Fir now 52" stump bears S.48°W., 21.8 ft. (rec. S.44°W., 21.8 ft.) This is only stump in vicinity that is this large.

New BT - 9" Incense cedar, bears S.17°E., 27.9 ft. mkd. 1/4 S11 CS BT.