

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10578)

A pine, 30" dia., for ¼ sec. cor., I mark ¼ S 35 on W & 36 on E side, from which

A fir, 24" dia., bears N.32°E., 75 lks., mkd: ¼ S36 BT.

A fir, 24" dia., bears S.89°W., 9 lks., mkd: ¼ S35 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton & Joel Sheriff - March 17, 1977 - C.S. File 59/31-19

Found - Orig. Pine corner tree is down and well decayed. Scribing visible on portion of log, "¼ S35".

A 32" Fir stump bears N.32°E., 49.5 ft. Open & find scribing on face & reverse, "S36 BT".

A 30" Fir stump bears S.89°W., 5.94 ft. Has a healed blaze.

Set - A 2½" Brass cap set 4" above ground surface stamped:
County Surveyors Office T 29 S 1 R 1 E
1977 ¼ S 35|S 36

Established by reference to accessories. Is located in stump hole of orig. corner tree.

New BTs- A 15" Sugar Pine bears S.52°30'W., 38.8 ft. scribed "1/4 S35 CS BT" on a double blaze.

A 18" D.Fir bears S.84°E., 92.0 ft. scribed "¼ S36 CS BT" on a double blaze.

Placed County BT tags on both trees.

Note - Corner lies 75 ft. North of the South edge of a clearcut unit on a small ridge top.