

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10631-2)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap marked:

T29S	R1E
S 14	S 13
S 23	S 24
1921	

from which

- A yew, 6" dia., bears N.47°E., 20 lks., mkd: T29S R1E S13 BT.
- A fir, 36" dia., bears S.69°E., 39 lks., mkd: T29S R1E S24 BT.
- A hemlock, 12" dia., bears S.73°W., 51 lks., mkd: T29S R1E S23 BT.
- A hemlock, 18" dia., bears N.41°W., 16 lks., mkd: T29S R1E S14 BT.

U.S. Forest Service, Tiller Ranger District 7/17/1961 - (Filed Nov. 16, 1973) - C.S. File 56/40-65

-
- Found - Brass cap
No information on BTs
 - Note - Best route to cor. use FS Rd. No. 291 or 2921.
Sec. line marker on Rd. 291, 9 chs north of corner