

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10634)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 11, 12, 13, & 14, with brass cap mkd

T29S | R1E
S 11 | S 12
S 14 | S 13
1921

from which

- A fir, 30" dia., bears N.1°E., 47 lks mkd: T29S R1E S12 BT
- A fir, 6" dia., bears S.61°E., 13 lks mkd: T29S R1E S13 BT
- A fir, 30" dia. bears S.58°W., 36 lks mkd: T29S R1E S14 BT
- A fir, 40" dia. bears N.23°W., 33 lks mkd: T29S R1E S11 BT

U.S. Forest Service, Tiller Ranger District - 1/22/1945 -
(Filed Nov. 16, 1973) - C.S. File 56/40-56

-
- Found - Brass cap
30" D.F. N.1°E., 47 lks., dead.
40" D.F. N.23°W., 33 lks.
6" D.F. S.61°E., 13 lks.
30" D.F. S.58°W., 36 lks.

Note - Best route to cor. use F.S. Rd. No. 2942