

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10636-7)

-----

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T29S	R1E
S 2	S 1
S 11	S 12
1921	

from which

- A fir, 24" dia., bears N.66°E., 20 lks mkd: T29S R1E S1 BT
- A fir, 18" dia. bears S.17°E., 36 lks mkd: T29S R1E S12 BT
- A fir, 30" dia., bears S.7°W., 42 lks mkd: T29S R1E S11 BT
- A cedar, 18" dia., bears N.17°W., 34 lks., mkd: T29S R1E S2 BT.