

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10638-9)

S.0°06'E., on a true line, bet. secs. 1 & 2 ...
36.05 chs.

Point for ¼ sec. cor. will fall on insecure ground; therefore, at this point, Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for witness cor. to the ¼ sec. cor., with brass cap marked

¼
S 2|S 1
WC
1921

from which

A fir, 30" dia., bears N.17°E., 42 lks., mkd: WC ¼ S1 BT.

A vine maple, 6" dia., bears S.18°W., 7 lks., mkd: WC ¼ S2 BT.

...10.19 chs.

True point for ¼ sec. cor. on low ground, subject to overflow, and liable to destruction by erosion of river bank; from this point, Cor. No. 6 HES No. 179, which is a granite stone, 10x12x8" above ground, firmly set, marked & witnessed as described in field notes of HES No. 179, bears N.5°54'E., 6.17 chs.; and U.S.L.M. No. 179, which is a granite stone, 10x9x7" above ground, firmly set, marked & witnessed as described in field notes of HES No. 179, bears S.46°18'W., 33.24 chs.

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-41

Never found.

DCSO VR Tracey C.S. File 54/82-87 - 11/1969 - S. Umpqua River has changed channels & wiped out most trees.