

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 601100

PRIMARY CORNER DESCRIPTION CC Secs 1 & 2 only; T30-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14102-3)

Set an iron post, 3 ft long, 2" dia., 27" in the ground, for closing cor. of secs. 1 & 2, with brass cap marked:

T29S R1E
S 36
S 2 | S 1
T30S R1E
C C
1937

from which

A Y.Pine, 36" dia., bears S.67°E., 34 lks., mkd: T30S R1E S1 CC BT.

An I.Cedar, 22" dia., bears S.37°W., 96 lks., mkd: T30S R1E S2 CC BT.

... the cor. of secs. 35 & 36 only, S. bdy. T29S R1E... bears S.89°57'W., 1.52 chs.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Walter Barton & Joel Sheriff - March 17, 1977 - C.S. File 59/31-11

Found - 1937 GLO brass cap properly marked 8" above ground.
A 37" Ponderosa Pine bears S.67°E., 22.44 ft. Has a healed blaze.

A 26" Incense Cedar bears S.37°W., 63.36 ft. scribing visible on partly healed blaze.

Placed County BT signs on both trees which are alive and well. DID NOT REMONUMENT CORNER.