

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10581)

-----  
Set a basalt stone 12x12x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A cedar, 20" dia., bears N.1°W., 25 lks., mkd: ¼ S24 BT.  
A fir, 8" dia., bears S.46°W., 32 lks., mkd: ¼ S25 BT.

Fd. & used on GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10611)

Douglas Co. Surveyors Office - Gary Langlitz - Peter Earle - Oct. 7, 1974 - C.S. File 57/8-9

-----  
Found - A basalt stone 12x12x8" with a "+" chiseled on top & a "¼" chiseled on the north edge of the top face. From which:  
An orig. 20" now 30" Incense Cedar bears N.1°W., 16.5 ft. alive and well healed.  
An orig. 8" D.Fir, now down, bears S.34°W., 21.1 ft. (rec. S.46°W. 21.1 ft.) The healed blaze is visible we do not open.

At the corner point we set a 1"x30" IP 26" in the ground with a Brass cap attached, mkd:

COUNTY SURVEYORS	T29S
OFFICE	¼ <u>S 24</u>
1974	S 25
	R1E

We place the orig. stone alongside the brass cap and mark the following new BTS:  
A 9" D.Fir bears S.80°W., 36.2 ft. scribed "¼ S25 CS BT"  
Compass declination setting: 20°East