

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10632-3)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap mkd: $\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$
1921

from which

A fir, 9" dia., bears N.51°E., 28 lks., mkd: $\frac{1}{4}$ S13 BT.

A fir, 40" dia., bears S.25°E., 27 lks., mkd: $\frac{1}{4}$ S24 BT.

U.S. Forest Service, Tiller Ranger District 1/8/1964 - (Filed Nov. 16, 1973) - C.S. File 56/40-60

Found - Brass cap
48" DF N.29°W., 18'
10" DF S.43°W., 18'

Note - Best route to cor. use FS Rd. No. 291. Should be between C.C. 29-2 and Cr.