

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 30, 31, & 36, T29-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO rec Vol 25 Pg 10576)

Set a basalt stone 18x12x5", 12" in the ground for cor. of secs. 25, 30, 31, & 36 mkd with 5 notches on N & 1 notch(es) on S edges, from which

- A fir, 7" dia., bears N.82°E., 23 lks mkd: T29S R2E S30 BT
- A fir, 10" dia. bears S.70°E., 20 lks mkd: T29S R2E S31 BT
- A fir, 12" dia. bears S.77°W., 20 lks mkd: T29S R1E S36 BT
- A madrone, 7" dia., bears N.15°W., 20 lks., mkd: T29S R1E S25 BT.

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10609)

The cor. of secs. 25, 30, 31, & 36 which is a basalt stone, 6x12x5" above ground, firmly set, marked & witnessed as described by the surveyor general, except that the NW BT is dead. I take new BT.

from the corner

- (Old BT) A fir, 8" dia., bears N.82°E., 23 lks mkd: T29S R2E S30 BT
- (Old BT) A fir, 12" dia. bears S.70°E., 20 lks mkd: T29S R2E S31 BT
- (Old BT) A fir, 14" dia. bears S.77°W., 20 lks mkd: T29S R1E S36 BT
- (New BT) A fir, 20" dia., bears N.8°W., 48 lks., mkd: T29S R1E S25 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz - Pete L. Earle - Oct. 1974 - C.S. File 57/8-6

Found - A basalt stone 14"x12"x5" (orig. 18"x12"x5") firmly set 9" in the ground, mkd. with a "+" on top, we do not find any notches on the stone.

From which

- An orig. 7" now 10" D.Fir bears N.82°E., 15.2 ft. scribing visible on unhealed blaze.
- An orig. 10" now 16" D.Fir bears S.70°E., 13.2 ft. well healed.
- An orig. 12" now 19" D.Fir bears S.77°W., 13.2 ft. well healed
- A D.Fir tree mkd. in a retracement survey, orig. 20" now 27" in diameter bears N.8°W., 31.7 ft. well healed.

There is no trace of the original NW bearing tree.

At the corner point we set a 1" x 30" Iron pipe with Brass cap attached mkd. continued next page

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 36; 30 & 31, T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

COUNTY SURVEYORS
OFFICE
1974

T 29 S
S 25 | S 30
S 36 | S 31
R1E R2E

And deposit the orig. stone alongside.
Compass declination setting: 20°East.