

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Cor. Secs. 24, 25, 19 & 30 T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO recs Vol 25 Pg 10577)

Set a basalt stone 12x10x6", 8" in the ground for cor. of secs. 19, 24, 25, & 30 mkd with 4 notches on N & 2 notch(es) on S edges, from which

A fir, 24" dia., bears N.25°E., 41 lks., mkd: T29S R2E S19 BT.

A cedar, 30" dia., bears S.48°E., 55 lks., mkd: T29S R2E S30 BT.

A fir, 16" dia., bears S.58°W., 25 lks., mkd: T29S R1E S25 BT.

A cedar, 24" dia., bears N.20°W., 42 lks., mkd: T29S R1E S24 BT.

FD & used on GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10610)

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 10/10/1974 - C.S. File 57/8-11

Found - A stone, 12x10x6", loosely set, mkd. with a chiseled "+" on top and 4 notches on the north face. We do not find the notches called for on the south face however, the stone has suffered fire damage in that area.

An orig. 30" Cedar, now 34" stump bearing S.48°E., 36.3 ft. We open blaze partially and find good scribing "S 2 E"

There is no remaining evidence of any other original BTs.

Set - An Iron pipe flush with the ground with brass cap attached mkd:

COUNTY SURVEYORS	T 29 S
OFFICE	<u>S 24 S 19</u>
1974	<u>S 25 S 30</u>
	R1E R2E

We place the orig. stone alongside the brass cap and set the following Bearing Object:

A boat spike, stamped with a "25" on top, driven in the top of a 36" fir stump bears S.55½°W. 29.0 ft

Note - This corner lies at the bottom of a SW slope in an old clearcut unit approx. 65 ft. north of a small creek, course N.50°W.