

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13; & 18 T29-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10620)

-----  
Set a basalt stone 20x10x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which  
A laurel, 12" dia., bears N.7°E., 24 lks., mkd: ¼ S18 BT.  
A chinquapin, 12" dia. bears N.60°W., 33 lks mkd: ¼ S13 BT  
No iron post available for this corner.

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-31

-----  
Never found.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Terrie Plouff & Teresa Buley, witnesses - 10/5/1981 - C.S. File 61/29-45

-----  
Found - Original stone (20x10x8"), now 16x8x6", protruding 6" out of ground with "¼" marked on the West face.  
BTs - Orig. 12", now 13" Madrone w/good scar, bears N.7°E., 15.8 ft. (Alive, good condition).  
Orig. 12", now 12" Chinquapin w/good scar, bears N.58°W., 21.8-ft. (Rec. N.60°W.) (Alive, good condition).  
Set - I reference the location of the orig. stone and set a Brass Cap protruding 12" at the same location, mkd: Douglas County Surveyor T29S R1E S13 S18 R2E 1981  
New BTs- 8" Fir bears N.85°E., 7.6 ft., scribed ¼ S18 CS BT in dbl. blaze  
9" Fir bears N.84°W., 35.1 ft., scribed ¼ S13 CS BT in dbl. blaze.  
I place stone along W. side of BC flush w/ground.