

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Township Corner

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10622-3)

-----

Point for Tp. cor. falls on sloping bedrock; impracticable to set iron post, and no stones available for supporting mound. Therefore, I cut a cross (x) at exact corner point, for cor. of Tps. 28 & 29S, Rs 1 & 2 E; with 6 grooves N, E, S, & W of cross, from which

- A fir, 7" dia. bears N.37°E., 32 lks. mkd: T28S R2E S31 BT
- A fir, 10" dia. bears S.64°E., 18 lks. mkd: T29S R2E S6 BT
- A fir, 20" dia. bears S.43°W., 25 lks. mkd: T29S R1E S1 BT
- A fir, 10" dia. bears N.11°W., 16 lks mkd: T28S R1E S36 BT

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-42

-----

Never found.