

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943010

PRIMARY CORNER DESCRIPTION Corner No. 1 HES 143

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914- DCSO records Vol. 28 Page(s) 12015)

-----  
Cor. No. 1, identical with cor. H/2 of listing survey No. 6-590, Tract 1, a post, mkd & witnessed as described by the listing surveyor, in place of which I set a porphyry stone, 24x10x8", 14" in the ground, for Cor. No. 1, mkd. 1 HES 143 on NE face, with a cross (+) on top; from which  
A fir, 8" dia., bears N.19°10'E., 27 lks.  
A hemlock, 6" dia., bears N.42°00'W., 2 lks.  
Both trees blazed and scribed 1 HES 143 BT.  
The NE cor. of sec. 13, T29S R1W WM, a stone, mkd. and witnessed as described by the Surveyor General, bears S.84°14'W., 151.13 chs.  
Pits & mound impracticable at this and all other cors.

Looked for/not fd. DCSO VRT 12/1969 - C.S. 54/82-92: would Fall in old cat road

Maurice E. Farr, USFS - July 1975 - M56-26

-----  
Set - 1"x36" gal. pipe with brass cap stamped: "T29S HES 143 COR. 1 PE 5188 R1E 1975" from which bears:  
A 9" Hemlock S.6°E., 8.8 ft. scribed 1 HES 143 BT.  
A 16" Hemlock S.80°W., 66.3 ft. scribed 1 HES 143 BT.