TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943020

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 143

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914- DCSO records Vol. 28 Page(s) 12016)

Cor. No. 2, identical with Cor. H/3 of listing survey 6-590, tract 1, a stake mkd. and witnessed as described by the listing surveyor, in place of which I set a porphyry stone, 24x12x6", 14" in the ground, for cor. 2, mkd. 2 HES 143 on SE face, with a cross (+) on top; from which

A fir, 15" dia., bears N.44°30'E., 36½ lks.
A fir, 20" dia., bears N.33°30'W., 31 lks.

Both trees blazed and scribed 2 HES 143 BT.
Pits & mound impracticable at this and all other cors.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - J. Heritage & V. Perron - 12/5/1969 - C.S. File 54/82-91

Found - Stumps of orig. BTs, as follows:
Orig. 15" now 24" Fir, N.44½°E., 24.1 ft. open & find scribe.
Orig. 20" now 30" fir N.33½°W., 20.5 ft. open & scribe visible.
No trace of old corner stone.

Set Brass cap at cor. mkd: COUNTY SURVEYORS T29S R1E
OFFICE 1969 COR #2/HES 143

New BTs- 20" Cedar N.80°E., 109.6 ft. mkd: " 2 HES 143 CS BT"
No other trees close. The East end of 16" culvert feeding pond bears S.10°E., 41.0 ft.

FD. BC & 1 BT, M.Farr, July 1975 - M56-26

Leonard Herzstein, USFS - April 1981 - C.S. File 61/19-23

Found - 1" I.P. firmly set projecting 4" above 2 ft. dia. mound of stone with 1969 brass cap properly marked.
Orig. D.Fir, 24" stump, N.44½°E., 24.1 ft. (to face) previously opened with scribe marks "HES 143 BT" visible.
A 30" 13. Fir stump, (orig.) bears N.33½°W., 20.5 ft. (to face) previously opened with scribe marks "2 HES 143" visible.
A 25" I.Cedar, bears N.80°E., 108.7 ft. (Rec. 109.6 ft.) with healed blaze.

New BT - A 9" D.Fir, N.3°W., 26.1 ft. marked "2 HES 143 CS BT" on double blaze.