

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943050

PRIMARY CORNER DESCRIPTION Cor. No. 5 HES 143

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914- DCSO records Vol. 28 Page(s) 12017)

Cor. No. 5, identical with Cor. H/11 of listing survey 16-97, a post mkd. and witnessed as described by the listing surveyor, in place of which I set a porphyry stone, 24x10x7" 14" in the ground, for Cor. No 5, mkd. 5 HES 143 on SE. face, with a cross (+) on top; from which

A fir, 18" dia., bears N.27°15'E., 99 lks.

A fir, 20" dia., bears N.14°07'W., 80 lks.

both trees blazed and scribed 5 HES 143 BT.

Pits & mound impracticable at this and all other cors.

Maurice E. Farr, USFS - July 1975 - M56-26

Found - Orig. corner stone in place with visible scribe HES 143 on SE face.

Set - 1"x36" galvanized pipe with Brass cap stamped T29S HES 143 COR. 5 PE 5188 R1E 1975. The orig. cor, stone is buried along the NW side of pipe. From which:

A 27" Fir, N.87°W., 121.1 ft. scribed 5 HES 143 BT.

A 8" Fir, N.5°15'E., 77.6 ft. scribed 5 HES 143 BT.