

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943130

PRIMARY CORNER DESCRIPTION Cor. No. 13 HES 143

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914- DCSO records Vol. 28 Page(s) 12020

-----  
Cor. No. 13, identical with Cor. H/2 of listing survey No. 6-590, Tract 2, a post, mkd. and witnessed as described by the listing surveyor, in place of which I set a porphyry stone, 26x14x8", 14" in the ground, for Cor. 13, mkd. 13 HES 143 on NE. face, with a cross (+) on top; from which -  
    A fir, 24" dia., bears S.29°00'W., 16 lks.  
    A fir, 10" dia., bears N.27°55'W., 12 lks.  
    both trees blated and scribed 13 HES 143 BT.  
Pits & mound impracticable at this and all other cors..

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - J. Heritage - 12/15/1969 - C.S. File 54/82-93

-----  
Found - Old corner stone, out of place, mkd: "3 HES 143"  
    Orig. 24", now 30" Fir stump, S.29°W., 10.6 ft. open & find scribe.  
    Orig. 10", now only decayed remains with reverse scribe, N.28°W., 7.9 ft.  
Set BC at cor. mkd: COUNTY SURVEYORS T29S R1E  
    (Reset stone alongside) OFFICE 1969 COR. #13 <HES 143  
New BTs- 7" D.Fir N.59°W., 43.8 ft. mkd: "13 HES 143 CS BT"  
    10" Maple N.84°E., 51.6 ft. mkd: "13 HES 143 CS BT"  
This corner lies on S side of small knoll & peak of roof of house bears S.50°E., approx. 200 ft.

FD. BC & 2 BTs by M.Farr, USFS - July 1975 - M56-26