

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943150

PRIMARY CORNER DESCRIPTION Cor. No. 15 HES 143

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914- DCSO records Vol. 28 Page(s) 12021)

Cor. No. 15, identical with Cor. H/4 of listing survey No. 6-590, Tract 2, a post, mkd. and witnessed as described by the listing surveyor, in place of which I set a porphyry stone, 24x12x9", 14" in the ground, for Cor. 15, mkd. 15 HES 143 on S face, with a cross (+) on top; from which
A fir, 18" dia., bears N.60°25'W., 79 lks.
A fir, 18" dia., bears N.18°15'W., 75 lks.
both trees blazed and scribed 15 H E 5 143 B T.
Pits & mound impracticable at this and all other cors.

Looked for/not fd. DCSO VRT 12/1969 - C.S. 54/82-94: Would fall in cleared area just below access road.

Maurice E. Farr, USFS - July 1975 - M56-26

Set - 1"x36" galv. pipe with Brass cap stamped "T29S HES 143 COR. 15 PE 5188 R1E 1975" from which bears:
A 14" pine N.26°W., 213.5 ft. scribed 15 HES 143 BT.
A 5" Fir N.16°45'E., 96.2 ft. scribed 15 HES 143 BT.