

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943220

PRIMARY CORNER DESCRIPTION Cor. No. 22 HES 143

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914- DCSO records Vol. 28 Page(s) 12024)

Set a porphyry stone, 2416x8", 14" in the round, for Cor. 22, mkd 22 HES 143 on SW face, - with a cross (+) ,on top; from which

 A hemlock, 14" dia., bears S.20°25'W., 53½ lks.
 A hemlock, 18" dia., bears N.43°10'W., 14 lks.
 both blazed and scribed 22 HES 143 BT.
Pits & mound impracticable at this and all other cors.

Looked for/not fd. DCSO VRT 12/1969 - C.S. 54/82-101:
Destroyed by cat logging - No OBTs or cor. stone fd.

Maurice E. Farr, USFS - July 1975 - M56-26

Set - 1"x36" galv. pipe with Brass cap stamped "T29S HES 143 22 23 BO PE 5188 R1E 1975" from which bears:

 A 9" Fir S.34°W., 29.8 ft scribed BO 22 & 23 HES 143 BT
 A 13" Fir N.68°30'E., 25.0 ft. scribed BO 22 & 23 HES 143 BT.
 BTs reference only bearing object, bearing object is 53.2' S66°10'E., from Corner 22.

1