

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943280

PRIMARY CORNER DESCRIPTION Cor. No. 28 HES 143

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12026

-----  
Cor. No. 28, identical with Cor, H/23 of listing survey No. 6-97, a post, mkd. and witnessed as described by the listing surveyor; in place of which I set a porphyry stone, 24x12x8" 14" in the ground, for Cor. 28, mkd. 28 HES 143 on NW face, with a cross (+) on top; from which  
    A hemlock, 16" dia., bears N.49°50'E., 19 lks.  
    A hemlock, 10" dia., bears S.4°15'W., 21 lks.  
        both trees blazed and scribed 28 HES 143 BT.  
Pits & mound impracticable at this and all other cors.

Maurice E. Farr, USFS - July 1975 - M56-26

-----  
Set - 1"x36" galv. pipe with Brass cap stamped "T29S HES 143 COR. 28 PE 5188 R1E 1975" from which bears:  
    A 5" Fir S.24°45'E., 15.7 ft. scribed 28 HES 143 BT.  
    A 6" Fir S.28°15'W., 40.0 ft. scribed 28 HES 143 BT.