

PRIMARY CORNER DESCRIPTION Cor. No. 30 HES 143

Alias 944050 Description Cor. No. 5 HES 144
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12027 & 12035-6 HES 144)

To Cor. No. 30, identical with Cor. H/31 of listing survey No. 6-97, identical with Cor. H/31 of listing survey No. 6-350, and will be identical with Cor. 5, HES 144, a post mkd. and witnessed as described by the listing surveyor; in place of which I set a porphyry stone, 24x16x12", 14" in the ground for Cor. 30, mkd. 30 HES 143 on NE. face, with a cross (+) on top; from which

A fir, 28" dia., bears S.7°45'E., 18 lks.

A fir, 36" dia., bears N.81°00'W., 48 lks.

both trees blazed and scribed 30 H E S 143 BT & 5 HES 144 BT. Pits & mound impracticable at this and all other cors.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 12/18/1969 - C.S. File 54/82-105

Found - No trace of corner stone or other Orig. BT.
Orig. 36" Fir, now 37" stump N.81°W., 31.7 ft. scribe visible on burned blaze.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS
(Flush with ground) OFFICE 1969 T29S R1E
COR. #30 HES 143 Cor. #5 HES 144

New BT - 24" Maple S.81°E., 143.5 ft. mkd: "5 HES 144 CS BT.
(most Westerly of 3 forks on one stump)

No other trees near.

Note - 1½" "+" on top of west end of 36" culvert pipe bears N.27½°W. 71.5 ft.

Corner is on east edge of USFS access road.

Fd. Brass cap by M. Farr, 7/1975 - M56-26

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Sept. 19, 1991 - C.S. File 64/17-10

Found - A 2¼" dia. DCSO brass cap on an iron pipe flush with ground.

36" now 30" dia. 2½ ft. high rotted D.Fir stump with an open blaze, no scribing visible, bears N.81°W., 31.7 ft. Orig BT. (agrees with record)

24" now 28" dia. Maple with a fully healed single blaze, bears S.84½°E., 143.5 ft. measurements go to westerly fork of multi-trunk Maple. (Rec. S.81°E., 143.5 ft.)1969 cont. next page

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943300

PRIMARY CORNER DESCRIPTION Cor. No. 30 HES 143

Alias 944050 Description Cor. No. 5 HES 144

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Culvert with "+" from 1969 not found.
New BTs- 10" dia D.Fir double blazed and scribed: "5 HES 144
CSBT" bears S.8¼°W., 77.9 ft.
12" dia. D.Fir double blazed and scribed "5 HES 144
CS BT" bears S.59½°W., 47.3 ft.
Corner lies approx. 10 ft. East of gravel road at fence
corner under gate.