

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 943310

PRIMARY CORNER DESCRIPTION Cor. No. 31 HES 143

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 143 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12027)

-----

Cor. 31, identical with Cor. H/1 of listing survey No. 6-590, Tract 1, a post mkd. and witnessed as described by the listing surveyor, in place of which I set a porphyry stone, 24x12x8", 14" in the ground for Cor. 31, mkd. 31 HES 143 on NE. face, with a cross (+) on top; from which

- A fir, 8" dia., bears S.12°10'W., 17 lks.
- A fir, 6" dia., bears S.79°30'W., 16½ lks.

both trees blazed and scribed 31 HES 143 BT.

Pits & mound impracticable at this and all other cors.

---

Maurice E. Farr, USFS - July 1975 - M56-26

-----

Set - 1"x36" galv. pipe with Brass cap stamped "T29S HES 143 COR. 31 PE 5188 R1E 1975" from which bears:

- A 6" fir S.27°15'E., 48.1 ft. scribed 31 HES 143 BT.
- A 6" fir S.23°30'W., 26.0 ft. scribed 31 HES 143 BT.