

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 944020

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 144

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 144 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12034

Cor. No. 2, identical with Cor, H/3 of listing survey List 6-350, an alder tree, 4" dia., mkd, and witnessed as described by Vernon V. Harpham, Assistant Forest Ranger. In place of tree, which I remove, I set a porphyry stone, 28x16x10", 18" in the ground, for Cor. No. 2, mkd. 2 HES 144 on S. face, with a cross (+) on top; from Which


- A fir, 16" dia., brs N.78°30'E., 49 lks.
- A fir, 28" dia., brs N.16°50'W., 25 lks.

both blazed and scribed 2 HES 144 BT.

Pits and mounds impracticable at this and all other cors.

Looked for Not fd by DCSO VRT, 12/1969 - C.S. 54/82-109: Destroyed by logging Road - No corner stone Fd or BTs

Maurice E. Farr, USFS - July 1975 - M56-25

Set - 1"x36" galvanized pipe with brass cap stamped: T29S HES 144 COR 2  PE 5188 R1E 1975, from which

- A 18" Fir N.10°45'E., 49.6' scribed 2 HES 144 BT.
- A 22" Fir N.24°45'E., 65.3' scribed 2 HES 144 BT.