TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 944030

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 144

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 144 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12034-5)

Cor. No. 3, identical with Cor. H/4 of listing survey, a small tree, mkd. and witnessed as described by Vernon V. Harphan, Assistant Forest Ranger; in place of tree, which I remove, I set a porphyry stone, 24x14x12", 14" in the ground, for Cor. No. 3, mkd. 3 HES 144 on S. face, with a cross (+) on top; from which

A fir, 30" dia., bears N.46°0'E., 62 lks.
A fir, 10" dia., bears N.16°0'W., 48 lks.
Both blazed & scribed 3 HES 144 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 12/18/1969 - C.S. File 54/82-104

Found - No trace of Corner Stone nor Other Orig. BT.
Orig. 30" Fir, now 40" Stump, N.46°E. 40.9 ft., open & find scribe.
Set Brass Cap at Cor. mkd: County Surveyors Office, 1969 T29S R1E Cor.#3 ╲╱ HES 144
New BT - 14" D.Fir N.71°W. 24.0 ft. mkd: 3 HES 144 CS BT
Marked a Boulder 9x6x4' above ground, a 4"+ & BO" facing corner, "+" is 2 ft. above ground & bears N.65°W. 5.7 ft. from corner. This lies 25 ft. south of USFS Access Road.

Fd. ok by M. Farr, July 1975 - M56-25