

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 944080

PRIMARY CORNER DESCRIPTION Cor. No. 8 HES 144

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 144 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12037)

Cor. No. 8, identical with Cor. H/26 of listing survey, a post, mkd. and witnessed as described by Vernon V. Harpham, Assistant Forest Ranger, in place of which I set a porphyry stone, 24x12x10", 14" in the ground, for Cor. No. 8, mkd. 8 HES 144 on West face, with a cross (+) on top; from which
 A fir, 10" dia., brs N.28°0'E., 52 lks.
 A fir, 16" dia., brs S.36°0'E., 11 lks.
 both blazed and scribed 8 HES 144 BT.
Pits and mounds impracticable at this and all other cors.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 12/24/1969 - C.S. File 54/82-115

Not Found
Cor. #8 would fall in logging road - no trace of OBTs or cor. stone.

Maurice E. Farr, USFS - July 1975 - M56-25

Set - 1"x36" galvanized pipe with brass cap stamped: T29S HES 144 COR 8)PE 5188 R1E 1975, from which
 A 8" fir N.83°E., 50.7' scribed 8 HES 144 BT.
 A 17" fir S.8°45'W., 79.5' scribed 8 HES 144 BT.