

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 944090

PRIMARY CORNER DESCRIPTION Cor. No. 9 HES 144

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 144 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12037)

Cor. No. 9 identical with Cor. H/27 of listing survey, fir tree, 30" dia., mkd. and witnessed as described by Vernon V. Harpham, Assistant forest Ranger. I mark the tree 9 HES 144 on NW. face, with a blaze on the NE and SW faces for Cor. No. 9;

from which

A fir, 16" dia., bears N.47°30'E., 55 lks.

A fir, 18" dia., bears S.56°30'E., 26 lks.

both blazed and scribed 9 HES 144 BT.

Pits and mounds impracticable at this and all other cors.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 12/24/1969 - C.S. File 54/82-112

Found - Orig. 30", now 36" Fir Corner Tree, now stump, we open & find scribe.

Orig. 16", now 20' Fir badly decayed stump, N.47½°E. 36.3 ft., with "B" scribe.

At a point 24" West of center of old corner tree, set

Set Brass Cap at Cor. mkd: County Surveyors T29S R1E

Office, 1969 Cor.#9 } HES 144

New BTs- 6" W.Fir S.74°E., 28.0 ft. mkd: "9 HES 144 CS BT"

9" D.Fir S.34°E. 49.1 ft. mkd: "9 HES 144 CS BT"

This corner lies 25 ft. east of Ash Creek, course S.

Maurice E. Farr, USFS - July 1975 - M56-25

Fd orig. 30" fir now 30" stump.

Fd. BC stamped: COUNTY SURVEYORS OFFICE T29S COR 9 < BO R1E 1969 - which lies N.79°W., 1.4' from corner stump.