

TOWNSHIP 29 RANGE 01e POINT IDENTIFIER # 944100

PRIMARY CORNER DESCRIPTION Cor. No. 10 HES 144

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 144 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12037)

Cor. No. 10, identical with Cor. H/28 of listing survey, a small tree, mkd. and witnessed as described by Vernon V. Harpham Assistant Forest Ranger; in place of tree, which I remove, I set a porphyry stone, 24x10x8", 14" in the ground, for Cor. No. 10, mkd. 10 HES 144 on NW. face, with a cross (+) on top; from which

A fir, 21" dia., bears N.26°40'E., 32 lks.

A fir, 48" dia., bears S.36°30'E., 7 lks.

both trees blazed and scribed 10 HES 144 BT.

Pits and mounds impracticable at this and all other cors.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 12/24/1969 - C.S. File 54/82-113

Found - Old corner Stone, in place, mkd: "10 HES 144".
Orig. 14", now 20" Fir Stump, N.26¾°E. 21.1 ft., open & find scribe.
Orig. 48", now 52" Fir Stump, S.36½°E. 4.6 ft., shows scar.

Set brass Cap at Cor. mkd: County Surveyors T29S R1E
(Reset stone alongside) Office, 1969 Cor.#10 } HES 144
New BTs- 10" Chinquapin S.89°E. 8.1 ft mkd: 10 HES 144 CS BT.
14" W.Fir N.16°E. 68.6 ft. mkd: 10 HES 144 CS BT.
This corner lies about 50 ft. East of Ash Creek, course SW.

Fd. Ok by M. Farr, July 1975 - M56-25