

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 944110

PRIMARY CORNER DESCRIPTION Cor. No. 11 HES 144

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 144 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12038)

Cor. No. 11, identical with Cor. H/29 of listing survey, a tree, mkd. and witnessed as described by Vernon V. Harpham, Assistant Forest Ranger; in place of the tree, which I remove, I set a porphyry stone, 24x12x10" 14" in the ground, for Cor. No. 11, mkd. 11 HES 144 on NW face, with a cross (+) on top; from which

A fir, 8" dia., bears N.47°0'E., 54 lks.

A fir, 12" dia., bears S.14°0'W., 52 lks.

both trees blazed and scribed 11 HES 144 BT.

Pits and mounds impracticable at this and all other cors.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 12/24/1969 - C.S. File 54/82-114

Found - Corner Stone, in place, mkd: " 11 HES 144".
Orig. 8", now 10" Fir, N.47°E. 35.6 ft., now 5 ft. high snag. we open and find scribing.
Orig. 12", now 20" W.Fir, S.14°W. 34.3 ft., alive, shows scar, We Tag.

Set Brass Cap at Cor. mkd: County Surveyors T29S R1E
(Reset Stone alongside) Office, 1969 Cor.#11 / HES 144
New BT - 14" W.Fir S.2°W., 14.7 ft. mkd: "11 HES 144 CS BT"
This corner lies 75 ft. S.45°E. of Ash Creek, course S.25°W.

Fd. Ok by M. Farr, July 1975 - M56-25