

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 944120

PRIMARY CORNER DESCRIPTION Cor. No. 12 HES 144

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 144 by Frank D. Maxwell, surveyor (FS), under special instructions dated April 27, 1914 - Surveyed June 1914 - DCSO records Vol. 28 Page(s) 12038)

-----  
Cor. No. 12, identical with Cor. H/30 of listing survey, a small tree mkd and witnessed as described by Vernon V. Harpham, Assistant Forest Ranger; in place of the tree, which I remove, I set a porphyry atone, 30x22x12", 20" in the ground, for Cor No. 12, mkd. 12 HES 144 on N. face, with a cross (+) on top; from which

A fir, 10" dia., brs. N.79°35'E., 39 lks.

A fir, 28" dia., brs. S.50°35'E, 18 lks.

both blazed and mkd. 12 HES 144 BT.

Pits and mounds impracticable at this and all other cors.

-----  
Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 12/24/1969 - C.S. File 54/82-115

Not Found

Cor. #12 fd. stump of one OBT - does not face properly - could be orig. bearing should have been SW instead of SE. We open & find "12 HES 144" scribe - no trace of old cor. stone or other OBT.

-----  
Maurice E. Farr, USFS - July 1975 - M56-25

Set - 1"x36" galvanized pipe with brass cap stamped: T29S HES 144 Cor. 12 √ PE 5188 R1E 1975 - from which bears:  
A 8" Hemlock S.31°30'W., 36.7' scribed 12 HES 144 BT.  
A 20" Maple N.35°W., 182.0' scribed 12 HES 144 BT.