

PRIMARY CORNER DESCRIPTION Cor. No. 3 Tract A; HES 179

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 179 by Frederick W. Rase, surveyor, under special instructions dated Dec. 17, 1915 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12045)

Cor. No. 3 (30 ft. above beginning of ascent) identical with cor. No. 3 of listing survey, which is a fir tree, 7" dia. I destroy all listing survey marks and mark the tree 3 HES 179 on side facing the claim; from which

A fir, 12" dia., bears S.57°50'E., 13 lks., marked X 3 HES 179 BT.

A fir, 45" dia., bears S.32°00'W., 49 lks., marked X 3 HES 179 BT.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. within the claim.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 11/25/1969 - C.S. File 54/82-86

Found - Orig. 7" now 8" W.Fir cor. tree, now snag, we open & find "179" scribed reverse.

Orig. 12" now 17" W.Fir, S.58°E., 8.6 ft. alive, shows good scar, we rescribe "3 HES 179 CS BT"

Only a hole in the ground where SW OBT would have been.

At a point 6" SE of the center of old cor. tree:

Set - 3/4"x30" IR 24" in ground & mk New BT:

12" W.Fir S.48°W., 23.3 ft. mkd: "3 HES 179 CS BT"

This corner lies 20 ft. above flat.

Gordon H. Long, USFS - For: USFS - Aug 1976/Jan 1978 - M65-77

Found - Orig. 7" now 8" fir snag corner tree with scribing "179" visible, from which:

A 3/4" IR S.45°E., 0.5'

Orig. 12" now 17" fir S.57°50'E., 8.58' with scribing visible "3 HES 179 CS BT"

12" fir S.48°W., 23.3' with scribing visible "3 HES 179 CS BT"

L. Herzstein for U.S. Forest Service, Sept. 20, 1994 - C.S. File 63/158 E

Found - Aug. 11, 1993: for corner 3 of HES 179, I found the original corner tree to now be a 10" white fir decayed stump with 2 decayed blazes.

20" D.Fir snag, bears S.57°50'E., 8.58 ft. with healed single blaze and a healed double blaze. Marked by Powell in 1969. continued next page

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 979030

PRIMARY CORNER DESCRIPTION Cor. No. 3 Tract A; HES 179

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

3/4" iron rod bears S.61°E., 0.6 ft, (rec. S.45°E., 0.5 ft.) projecting 12" above the ground with a center punch on top.
12" W.Fir, bears S.48°W., 22.9 ft. (rec. 23.3 ft.) with a healed double blaze.

Set - Aug. 29, 1994: I removed the decayed corner tree and in its place I set a 2½" diameter alum. post, 30" long, 30" in the ground with a 2½" diameter magnetized alum. cap attached and marked "T29S R1E COR 3 HES 179 LS 2150 1994"

New BT- 5" Yewwood, bears S.27°20'E., 11.9 ft. scribed "3 HES 179 BT" on a single blaze. A 3/4" diameter brass washer stamped LS 2150 is nailed flush to the BT blaze.

Note - Bearing tree measurements are to the center of the rootcrown and diameters are at breast height. The bearings are true and were rounded to the nearest 10 minutes computed from the control traverse. I determined the magnetic declination to be 14½° east