

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 979060

PRIMARY CORNER DESCRIPTION Cor. No. 6 Tract A; HES 179

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 179 by Frederick W. Rase, surveyor, under special instructions dated Dec. 17, 1915 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12046-7)

-----

Set a granite stone, 24x12x8", 14" in the ground, over a stone marked with a cross, for cor. No. 6 of this surveys marked 6 HES 179 on side facing the claim; from which

    An ash, 12" dia., bears N.27°30'W., 22 lks., marked X 6 HES 179 BT.

    An ash 16" dia., bears S.36°30'E., 79 lks., mkd X 6 179 BT

Raised a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. within the claim.

Gordon H. Long, USFS - For: USFS - Aug 1976/Jan 1978 - M65-77 & C.S. File 58/162-5 A-G

-----

No original corner evidence remains of this corner. The proportioned location of the corner falls in the South Umpqua Road. The proportioned location was monumented and witnessed. Set - 1"x24" galv. pipe with a 2½" brass cap mkd:

    T29S R1E Cor 6 / HES 179 RPLS 1017 1976

    Cap is 0.5' below road surface.

    A 14" maple N.43°30'W., 42.7' scribed "6 HES 179 BT"

    A 18" ash N.1°30'E., 75.7' scribed "6 HES 179 BT"