

PRIMARY CORNER DESCRIPTION Cor. No. 7 Tract A; HES 179

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 179 by Frederick W. Rase, surveyor, under special instructions dated Dec. 17, 1915 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12047)

-----  
Set a granite stone, 28x10x10", 18" in the ground, over a stone marked with a cross, for cor. No. 7 of this survey, marked 7 HES 179 on side facing the claim; from which  
    An ash, 22" dia., bears N.27°30'W., 22 lks., mkd X 7 HES 179 BT.  
    An ash, 16" dia., bears S.36°30'E., 79 lks., mkd. X 7 HES 179 BT.  
Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft., within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 12/1969 - C.S. File 54/82-90

-----  
Reported as not found.  
Corner #7 (& 9) Nothing Fd. at least one OBT for each cor. would fall in river.

Gordon H. Long, USFS - For: USFS - Aug 1976/Jan 1978 - M65-77 & C.S. File 58/162-5 A-G

-----  
The original corner stone was found set solidly in place. Evidence of both bearing trees was found. The corner stone was replaced with a brass cap monument and new bearing trees blazed and scribed.  
Found - Orig. stone, 10x10x28" firmly in place, 12" under the ground surface, mkd "X" on top and "7 HES 179" on the NW face.  
    Orig. 16" now 24" Ash with "BT" visible on partly healed blaze, bears S.34°E., 52.14' (Rec. S.36°30'E., 42.14') rescribe "X BT" on bark  
    Rotted stump of orig. Ash BT bears N.21°W., 14.52' (rec. N.27°30'W., 14.52')  
Set - 1"x36" galv. pipe with a 2½" brass cap stamped:  
    T29S R1E COR 7// HES 179 RPLS 1017 1976  
A memorial stone marked "X" set under the galv. pipe. (The orig. corner stone buried alongside)  
From which:  
A 14" ash, N.36°E., 13.5' barked scribed "X BT"  
A 26" D.Fir S.60°30'E., 85.8' scribed "7-9 HES 179 BT"