

PRIMARY CORNER DESCRIPTION Cor. No. 11 Tract B; HES 179

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

HES No. 179 by Frederick W. Rase, surveyor, under special instructions dated Dec. 17, 1915 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12048)

-----  
Set a granite stone, 25x8x8", 15" in the ground, over a stone mkd with a cross for cor. No. 11 of this survey, marked 11 HES 179 on side facing the claim; from which  
A yew, 8" dia., bears N.89°15'W., 39 lks., mkd X 11 HES 179 BT.  
A cedar, 16" dia., bears N.25°30'W., 57 lks. mkd X 11 HES 179 BT.  
Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 12/1969 - C.S. File 54/82-90

-----  
Reported as not found.  
Probably destroyed by road - & river course change

Gordon H. Long, USFS - For: USFS - Aug 1976/Jan 1978 - M65-77 & C.S. File 58/162-5 A-G

-----  
Found - Orig. stone 8x8x25" firmly in place 6" under the gourd surface, mkd with an "X" on top and "11 HES 179" on the SE face.  
No BT evidence remaining.  
Set - 1"x36" galv. pipe with a 2½" brass cap stamped: "T29S R1E COR 11 HES 179 RPLS 1017 1976" A memorial stone, mkd "X", set under the galv. pipe (The orig. corner stone buried alongside) from which  
A 42" D.Fir N.3°15'E., 109.56' scribed "11 HES 179 X BT"  
A lava rock outcrop 3'x4'x3' above the ground, N.63°W., 91.08' mkd "X BR" 1 ft. above ground in the lower left quadrant.

L.Herzstein for U.S. Forest Service, 9/19/1994 - C.S. File 63/158 G

-----  
Found - Sept. 19, 1994: For corner 11 of HES 179, I found a 1" iron post, firmly set, projecting 3" above a 3 ft. dia. mound of stone, with a 2½" brass cap attached and marked as shown on M65-77.  
A 42" D.Fir bears N.3°15'E., 109.56 ft. with no scribe marks visible on a partially healed double blaze. continued next page

PRIMARY CORNER DESCRIPTION Cor. No. 11 Tract B; HES 179

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A 3'x4'x3' high rock outcrop bears N.63°W., 91.08 ft. with 3" high marks "X BR" visible 1 ft. above the ground in the lower right quadrant (rec. lower left quadrant). Bearing and distance are to the "X"

A 1½" dia. alum. cap bears S.61°30'W., 8.8 ft. marked "R/W" and attached to a 5/8" rebar, firmly set, projecting 2" above the ground for right-of-way point P.O.C. 647+69.53, Right.

A steel fence post bears N.47°E., 2.6 ft. firmly set, projecting 4 ft. above the ground as a guard post with Forest Service signs #54-2 and 54-4 attached.

New BTs- 7" D.Fir bears S.61°40'E., 4.7 ft. scribed "11 HES 179 BT" on a double blaze.

11" D.Fir bears S.65°30'W., 16.2 ft. scribed "11 HES 179 BT" on a double blaze.

Note - Bearing tree measurements are to the center of the rootcrown and diameters are at breast height. The bearings are true and were rounded to the nearest 10' computed from the control traverse. I determined the magnetic declination to be 24¼° east at this corner. A 3/4" diameter brass washer stamped L.S. 2150 is nailed flush to the BT blaze on the new bearing trees.

The corner and new bearing trees are south of South Umpqua Road. The 1978 bearing trees are north of the road.