

PRIMARY CORNER DESCRIPTION Cor. No. 13 Tract B; HES 179

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 179 by Frederick W. Rase, surveyor, under special instructions dated Dec. 17, 1915 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12049)

Cor. No. 13, identical with Cor: No. 4 of listing survey, which I destroy, and, in its place
Set a sandstone, 26x12x8", 16" in the ground, over a stone marked with a cross for cor. No. 13 of this survey, mkd 13 HES 179 on side facing the claim; from which
 A fir, 10" dia. bears N.74°15'E., 39 lks., mkd X 13 HES 179 BT.
 A maple, 12" dia., bears S.69°30'W., 69 lks., mkd X 13 HES 179 BT.
Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 12/1969 - C.S. File 54/82-90

Reported as not found.
Probably destroyed by road - & river course change

Gordon H. Long, USFS - For: USFS - Aug 1976/Jan 1978 - M65-77 & C.S. File 58/162-5 A-G

Found - The original corner stone (8x12x26", mkd with an "X" and "13 HES 179) was found; however, it was out of place, apparently disturbed by logging activities.
No bearing tree evidence was found.
The proportioned corner point is monumented with a brass cap monument, and new bearing trees blazed and scribed.
Set - 1"x36" gal. pipe with a 2½" brass cap stamped:
 "T29S R1E COR 13 HES 179 RPLS 1017 1979" A memorial stone, mkd: "X", set under the galv. pipe (The orig. corner stone buried alongside)
 FROM WHICH
 A 8" D.Fir S.46°w., 24.42' scribed "X BT"
 A 10" D.Fir N.27°30'W., 28.38' scribed "13 HES 179 X BT"

Fd. Ok, 9/20/1994 by L. Herzstein, C.S. File 63/158-H