

PRIMARY CORNER DESCRIPTION Cor. No. 15 Tract B; HES 179

Alias _____	Description <u>M C Rt. Bank South Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 179 by Frederick W. Rase, surveyor, under special instructions dated Dec. 17, 1915 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12050

-----  
Cor. No. 15, on right bank of South Umpqua River, identical with Cor. No. 6 of listing survey, which I destroy and in its place. Set a granite stone 26x9x6", 16" in the ground, over a stone marked with a cross for meander corner and cor. No. 15 of this survey, marked M C on side facing river and 15 HES 179 on side facing the claim; from which

An alder, 14" dia., bears N.42°45'E., 45 lks., marked X 15 HES 179 M C B T.

A fir, 24" dia., bears N.72°15'W., 16 lks., mkd X 15 HES 179 M C B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, on lines 3½ ft. distant from corner.

-----  
Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 12/1969 - C.S. File 54/82-90

No trace, High water of river would have destroyed this cor.

-----  
Douglas Co. Surveyors Office - Clell Goodwin - Gary Langlitz - Lenora Ladig - 12/11/1975 - C.S. File 57/39-31

Found - A 26"x9"x6" stone marked with an MC on the river side and 15 HES 179 on the side facing the claim, also a stone under this stone which is marked with an X. from which

An Orig. 24" now 30" fir with good scar bears N.72¼°W., 10.6 ft.

A mound of stone 2'x2'x1' high with a 1' axle in the center bears N.72°W., 4.2 ft.

Set - A 1"x30" IP with brass cap stamped: T29S R1E  
DOUGLAS CO SURVEYOR COR 15 > WC\*  
1975 HES 179

from which:

A 26" D.Fir scribed "X 15 HES 179 MC CS BT" in a double blaze bears S.41°W., 55.2 ft.

Note - Compass declination 20°E.

\*Per M65/77 MC not WC - JC 1/13/2012, DCSO

-----  
Fd. Ok by Gordon H. Long, USFS - For: USFS - Aug 1976/Jan 1978 - M65-77 & C.S. File 58/162-5 A-G

continued next page

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 979150

PRIMARY CORNER DESCRIPTION Cor. No. 15 Tract B; HES 179

Alias \_\_\_\_\_ Description M C Rt. Bank South Umpqua River  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

L.Herzstein for U.S. Forest Service, 9/19/1994 - C.S. File 63/158 D

-----

- Found - 2½" dia. brass cap attached to a 1" dia. iron post, firmly set, projecting 6" above a 3 ft. dia. mound of stone. Brass cap marked as shown on C.S. file 57/39 by DCSO in 1975. The corner is 3 ft. from the edge of the bank of Quartz Creek.
- 44" D.Fir bears N.33°W., 22.0 ft. with a healed single blaze. (rec. 24" D.Fir marked "HW 6" bears N.33°W., 36 links) (1913)
- 34" D.Fir bears N.72¼°W., 10.6 ft. with a healed single blaze. (1916)
- 2 ft. dia. mound of stone bears N.84°W., 4.2 ft. (rec. N.72°W. per C.S. file 57/39) with a 1" dia. axle projecting 2" above the mound of stone (bearing is to the axle). (1916)
- 30" D.Fir bears S.33°20'W., 54.8 ft. with a healed double blaze. (rec. S.41°W., 55.2 ft. per C.S. file 57/39) (1975)
- New - An alum. post bears N.49°30'W., 3.8 ft., firmly set, projecting 4 ft. above the ground with Forest Service signs #54-2 and #54-9 attached.
- Note - The magnetic declination was found to be 17¾° east.