



TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 979190

PRIMARY CORNER DESCRIPTION WC Cor. No. 19 Tract B; HES 179

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set - 1" I.P, 30" long 27" in the ground with brass cap mkd:  
COUNTY SURVEYORS T29S R1E  
OFFICE Cor. 19  
1975 HES 179  
Wit. Cor.  
S.54°E. 188 FT

We leave the aforementioned bearing tree intact and make no reference to it concerning the witness corner now being set. New BTs- 24" I.Cedar bears S.17½°W., 91.2 ft. scribed "WC 19 HES 179 CS BT". This tree stands approx. 100 ft. southerly of South Umpqua Road.

26" D.Fir bears N.59°E., 98.2 ft. scribed "WC 19 HES 179 CS BT" This tree stands approx 30 ft. southerly of South Umpqua Rd.

37" R.Cedar bears N.3½°W.. 89.9 ft. scribed "WC 19 HES 179 CS BT". This tree stands approx 20 ft. Northerly of South Umpqua Road.

Note - This witness corner lies on the flat approx 30 ft. southerly of South Umpqua Road.

Fd. Ok G. Long -Aug 1976/Jan 1978 - M65-77 & CS 58/162-5 A-G

Leonard E. Herzstein, L.S. #2150 - For: U.S.D.A. Forest Service - July 1993 thru Oct. 1994 - C.S. File 63/158-2

Found - 1" iron post, firmly set, projecting 2" above the ground, w/2½" brass cap attached and marked as shown 1975 renewal

32" D.Fir, bears N.56°50'E., 98.2', (rec. N.59°E.) with a healed double blaze.

30" I.Cedar, S.14°45'W., 91.2', (rec. S.17½°W.) with a healed double blaze.

40" R.Cedar, bears N.5°50'W., 89.5', (rec. N.3½°W., 89.9') with scribe marks "HES 179" "CS BT" visible on a partially healed double blaze.

And a guard post I set:

A steel angle iron, firmly set, projecting 4' above the ground, bears S.27°E., 1.0', with D.C.S.O. sign "Survey Marker" and Forest Service sign no 54-4 attached.

The magnetic declination was found to be 29°E.