

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 979200

PRIMARY CORNER DESCRIPTION Cor. No. 20 Tract B; HES 179

Alias _____	Description <u>MC South Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>HES No. 179 by Frederick W. Rase, surveyor, under special instructions dated Dec. 17, 1915 - Surveyed September 1916 - DCSO records Vol. 28 Page(s) 12052)</p> <p>-----</p> <p>Cor. No. 20, identical with cor. No. 1 of listing survey, which I destroy, and in its place Set a granite stone, 26x8x8", 16" in the ground, over a stone marked with a cross for meander cor. and cor. No. 20 of this survey, marked MC on side facing river and 20 HES 179 on side facing the claim; from which     An alder, 14" dia., bears S.19°30'W., 66 lks., marked X 20 HES 179 MC BT. No other bearings available. Raise a mound of stone, 3½ ft. base, 2 ft. high, on line, 3½ ft. northwest of cor.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 12/1969 - C.S. File 54/82-90</p> <p>-----</p> <p>No trace, on gravel bars - High water probably destroyed this cor</p>
<p>Gordon H. Long, USFS - For: USFS - Aug 1976/Jan 1978 - M65-77 &amp; C.S. File 58/162-5 A-G</p> <p>-----</p> <p>Found - Orig. 14" now 22" Alder snag with partly healed blaze bears S.19°30'W., 43.56 ft. No scribing visible. Set - A 5½ ft. metal fence post 4 ft. into the ground in a mound of stone (corner subjected to frequent erosive flooding) From which Bears:     A 40" Cedar, S.82°30'W. , 39.0 ft. scribed "Cor 20 HES 179"     A 16" Alder, N.49°E., 49.9 ft. scribed "Cor 20 HES 179 BT".</p>
<p>1</p>